



ARTUBA[®]

Tractor

BENEFITS

- Increased Stability & Tyre Mileage.
- Increased Durability / Puncture Protection & Fit for Multiple Operations.
- Best Performance on "On & Off-Road" Application / Longer Total Tyre Life.
- Better Traction / Self-Cleaning.
- Maximum Longevity and Consistent Shape Integrity.
- Zero Wheel Slip / Excellent Stability with] Better Durability.
- Less Driver Exhaustion & Longer Tyre Life.





FEATURES

**Bigger Tyre with
Broader Tread**

**Optimum Curved
& Pyramid Lugs**

**Extra Rubber at
center with
Optimum (20) Lugs**

Attractive Mud Cracker

Strong Nylon Casing

Strong & Wide Bead




TRA Code
R-4

Size	Rim Alt Rim	Tyre Type	Unloaded inflated dimension		Static Loaded Radius (mm/in)	Rolling circumference (mm/in)	PR Load Index Speed Symbol	Inflation Pressure (bar psi)	Recommended load, kg/lbs	
			SW(mm/in)	OD (mm/in)					Speed, kmph/mph	
									30	
									19	
9.5-24	W8 W7 W8H	TT	241	1050	491 19.3	3150 124.0	8 112A6	2.8 41	1120 2469	
			9.5	41.3			10 116A6	3.5 51	1250 2756	
11.2-24	W10	TT	284	1105	512 20.1	3370 132.6	8 116A6	2.4 35	1250 2756	
			11.1	43.5			10 120A6	3.0 44	1400 3086	
12.4-24	W11	TT	315 12.4	1160 45.6	543 21.3	3480 137.0	6 115A6	1.7 25	1215 2679	
							8 121A6	2.3 33	1450 3197	
							12 128A6	3.5 51	1800 3968	
14.9-24	W13 W11 W12	TT	378 14.8	1265 49.8	574 22.6	3545 139.5	8 128A6	1.8 26	1800 3968	
							12 135A6	2.6 38	2180 4806	
13.6-28	W12 W11	TT	345 13.5	1310 51.5	613 24.1	3930 154.7	8 125A6	2.0 29	1650 3638	
							10 127A6	2.2 32	1750 3858	
							12 128A6	2.3 33	1800 3968	
14.9-28	W13 W11 W12	TT	378 14.8	1365 53.7	639 25.1	4095 161.2	8 130A6	1.8 26	1900 4189	
							10 132A6	2.1 30	2000 4409	
18.4-26	W16L W15L	TT	467 18.4	1450 57	647 25.5	4370 172	10 142A6	1.9 28	2650 5842	
							12 146A6	2.3 33	3000 6614	
16.9-30	W15L W14L	TT	429 16.8	1485 58.4	695 27.3	4455 175.3	8 137A6	1.7 25	2300 5071	
							10 140A6	2.0 29	2500 5512	
							12 144A6	2.4 35	2800 6173	
							16 149A6	3.2 46	3250 7165	
18.4-30	W15L W14L	TT	467 18.3	1550 61.0	725 28.5	4650 183.0	10 145A6	1.8 26	2900 6393	
							12 149A6	2.3 33	3250 7165	
							16 154A6	2.9 42	3750 8267	



PROWLER[®]

Tractor

BENEFITS

- Optimum Traction and soil penetration
- Strong Carcass to carry higher load & safeguard from external damage
- Multi Angled lug provides traction, free rolling & smooth riding





TRA Code

R1

Size	Rim Alt Rim	Tyre Type	Unloaded inflated dimension		Static Loaded Radius (mm/in)	Rolling circumference (mm/in)	PR Load Index Speed Symbol	Inflation Pressure (bar psi)	Recommended load, kg/lbs	
			SW(mm/in)	OD(mm/in)					Speed, kmph/mph	
									20	20
									12	12
8.3-32	W7 W6	TT	211 8.3	1195 47	565 22.2	3574 141	6 105A6	2.4 35	925 2039	
							8 111A6	3.2 47	1090 2403	
9.5-32	W8 W7	TT	240 9.4	1250 49.2	585 23.0	3740 147.2	6 106A6	2.1 31	950 2094	
16.9-34	W15L	TT	429 16.9	1587 62.5	731 28.8	4747 186.9	8 134A8	1.7 25		2120 4674
							10 138A8	1.9 28		2360 5203
18.4-34	W16L W15L	TT	467 18.4	1655 65.2	758 29.8	4950 194.9	8 137A8	1.4 20		2300 5071
							12 146A8	2.2 32		3000 6614
12.4-36	W11L W10	TT	315 12.4	1465 57.7	684 26.9	4380 172.4	6 117A8	1.7 25		1285 2833
							8 123A8	2.3 33		1550 3417
							10 127A8	2.9 42		1750 3858
							14 135A8	4.1 60		2180 4806



Size	Rim Alt Rim	Tyre Type	Unloaded inflated dimension		Static Loaded Radius (mm/in)	Rolling circumference (mm/in)	PR Load Index Speed Symbol	Inflation Pressure (bar psi)	Recommended load, kg/lbs	
			SW(mm/in)	OD(mm/in)					Speed, kmph/mph	
									20	20
									12	12
13.6-36	W12 W11	TT	345 13.6	1514 59.6	705 27.8	4530 178.3	6 125A6	1.6 23	1650 3638	
							8 129A6	2.0 29	1850 4079	
							10 134A6	2.5 36	2120 4674	
13.6-38	W12 W11	TT	345 13.6	1565 61.6	730 28.7	4680 184.3	6 126A6	1.6 23	1700 3748	
							8 131A6	2.0 29	1950 4299	
							10 136A6	2.5 36	2240 4938	
15.5-38	W14L	TT	395 15.5	1570 61.8	732 28.8	4712 185.5	6 124A8	1.4 20		1600 3527
							8 129A8	1.8 26		1850 4079
							10 134A8	2.3 33		2120 4674
16.9-38	W15L W14L	TT	430 16.9	1690 66.5	782 30.8	5052 198.9	8 141A6	1.7 25	2575 5677	
							10 143A6	2.0 29	2725 6007	
15.5-38	W16L W15L	TT	467 18.4	1755 69.1	810 31.9	5250 206.7	8 139A8	1.4 20		2430 5357
							12 149A8	2.2 32		3250 7165
							14 151A8	2.5 36		3450 7606



FEATURES

High traction with deep penetration and lower wear rate

Stronger tyre with high contact patch

**Nylon casing
Provides better dimensional stability**

Maintains best casing integrity

