

MAXAM MS950

BIAS PLY TRACTOR TIRE R1

Designed primarily for compact tractor dryfield operations.

- ▶ Exceptional sidewall support and driving force, paired with an excellent puncture-resistant compound for extended service life.
- ▶ High-angle lug design delivers superior traction. The high lug density in the crown center reduces ground pressure, minimizing center wear and vibration during operation.
- ▶ Self-cleaning tread grooves prevents mud buildup.
- ▶ Wide contact surface enhances stability and flotation.
- ▶ Contoured groove base combines durability with an aesthetic appearance.
- ▶ Premium compound significantly improves puncture resistance and aging resistance.

TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



| Size    | PR | LI/SS | TYPE | RIM (Rec.) | S.W. |     | O.D. |      | S.L.R. |     | R.C.  |      | TREAD DEPTH<br>32NDS<br>mm | Lugs | Inflation Pressure<br>kPa<br>psi | Load Capacity<br>kg<br>lbs |
|---------|----|-------|------|------------|------|-----|------|------|--------|-----|-------|------|----------------------------|------|----------------------------------|----------------------------|
|         |    |       |      |            | in   | mm  | in   | mm   | in     | mm  | in    | mm   |                            |      |                                  |                            |
| 13.6-28 | 8  | 125A6 | TT   | W12        | 13.6 | 345 | 51.6 | 1310 | 23.8   | 605 | 155.3 | 3945 | 46.6                       | 19x2 | 200                              | 1650                       |
|         |    |       |      |            |      |     |      |      |        |     |       |      | 37.0                       |      | 29                               | 3638                       |
| 14.9-24 | 8  | 127A6 | TT   | W13        | 14.9 | 378 | 49.8 | 1265 | 22.6   | 575 | 150.4 | 3820 | 45.4                       | 18x2 | 180                              | 1760                       |
|         |    |       |      |            |      |     |      |      |        |     |       |      | 36                         |      | 26                               | 3880                       |
|         | 10 | 128A6 | TT   | W13        | 14.9 | 378 | 49.8 | 1265 | 22.6   | 575 | 150.4 | 3820 | 45.4                       | 18x2 | 180                              | 1900                       |
|         |    |       |      |            |      |     |      |      |        |     |       |      | 36                         |      | 26                               | 4189                       |
| 14.9-26 | 8  | 128A6 | TT   | W13        | 14.9 | 378 | 51.8 | 1315 | 23.4   | 595 | 156.1 | 3966 | 47.9                       | 19x2 | 180                              | 1820                       |
|         |    |       |      |            |      |     |      |      |        |     |       |      | 38.0                       |      | 26                               | 4010                       |
| 14.9-28 | 8  | 129A6 | TT   | W13        | 14.9 | 378 | 53.7 | 1365 | 24.7   | 628 | 160.9 | 4086 | 47.9                       | 20x2 | 180                              | 1880                       |
|         |    |       |      |            |      |     |      |      |        |     |       |      | 38.0                       |      | 26                               | 4145                       |
| 14.9-30 | 10 | 135A6 | TT   | W13        | 14.9 | 378 | 55.7 | 1415 | 25.6   | 650 | 170.6 | 4333 | 47.9                       | 20x2 | 230                              | 2190                       |
|         |    |       |      |            |      |     |      |      |        |     |       |      | 38.0                       |      | 33                               | 4830                       |
| 15-24   | 10 | 144A6 | TT   | W14        | 16.1 | 410 | 52.4 | 1330 | 23.7   | 603 | 158.3 | 4020 | 42.2                       | 17x2 | 280                              | 2800                       |
|         |    |       |      |            |      |     |      |      |        |     |       |      | 33.5                       |      | 41                               | 6175                       |
|         | 14 | 151A6 | TT   | W14        | 16.1 | 410 | 52.4 | 1330 | 23.7   | 603 | 158.3 | 4020 | 42.2                       | 17x2 | 410                              | 3500                       |
|         |    |       |      |            |      |     |      |      |        |     |       |      | 33.5                       |      | 60                               | 7720                       |
| 16.9-28 | 12 | 138A6 | TT   | W15L       | 16.9 | 430 | 56.5 | 1435 | 25.2   | 641 | 168.1 | 4271 | 49.1                       | 20X2 | 200                              | 2380                       |
|         |    |       |      |            |      |     |      |      |        |     |       |      | 39.0                       |      | 29                               | 8550                       |

TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



| Size    | PR | LI/SS | TYPE | RIM (Rec.) | S.W. |     | O.D. |      | S.L.R. |     | R.C.  |      | TREAD DEPTH<br>32NDS<br>mm | Lugs | Inflation Pressure<br>kPa<br>psi | Load Capacity<br>kg<br>lbs |
|---------|----|-------|------|------------|------|-----|------|------|--------|-----|-------|------|----------------------------|------|----------------------------------|----------------------------|
|         |    |       |      |            | in   | mm  | in   | mm   | in     | mm  | in    | mm   |                            |      |                                  |                            |
| 16.9-30 | 8  | 137A6 | TT   | W15L       | 16.9 | 430 | 58.5 | 1485 | 26.5   | 672 | 176.3 | 4478 | 46.6                       | 21x2 | 170                              | 2300                       |
|         |    |       |      |            |      |     |      |      |        |     |       |      | 37.0                       |      | 25                               | 5070                       |
|         | 10 | 139A6 | TT   | W15L       | 16.9 | 430 | 58.5 | 1485 | 26.5   | 672 | 176.3 | 4478 | 46.6                       | 22x2 | 200                              | 2455                       |
|         |    |       |      |            |      |     |      |      |        |     |       |      | 37.0                       |      | 29                               | 5415                       |
| 16.9-34 | 10 | 141A6 | TT   | W15L       | 16.9 | 430 | 62.4 | 1585 | 28.2   | 717 | 188.2 | 4780 | 49.1                       | 20x2 | 200                              | 2605                       |
|         |    |       |      |            |      |     |      |      |        |     |       |      | 39.0                       |      | 29                               | 5680                       |
| 18.4-30 | 12 | 149A6 | TT   | W16L       | 18.1 | 460 | 61.0 | 1550 | 26.8   | 682 | 179.0 | 4546 | 51.7                       | 20X2 | 230                              | 3250                       |
|         |    |       |      |            |      |     |      |      |        |     |       |      | 41.0                       |      | 33                               | 7165                       |
| 18.4-34 | 12 | 151A6 | TT   | W16L       | 18.4 | 467 | 65.2 | 1655 | 28.6   | 726 | 190.7 | 4843 | 51.7                       | 22X2 | 230                              | 3450                       |
|         |    |       |      |            |      |     |      |      |        |     |       |      | 41.0                       |      | 33                               | 7606                       |
| 18.4-38 | 10 | 148A6 | TT   | W16L       | 18.4 | 467 | 69.1 | 1755 | 31.6   | 802 | 207.4 | 5268 | 51.7                       | 24x2 | 180                              | 3165                       |
|         |    |       |      |            |      |     |      |      |        |     |       |      | 41.0                       |      | 26                               | 6980                       |
|         | 12 | 152A6 | TT   | W16L       | 18.4 | 467 | 69.1 | 1755 | 31.6   | 802 | 207.4 | 5268 | 51.7                       | 24x2 | 230                              | 3575                       |
|         |    |       |      |            |      |     |      |      |        |     |       |      | 41.0                       |      | 33                               | 7880                       |
| 20.8-38 | 12 | 156A6 | TT   | W18L       | 20.8 | 528 | 72.2 | 1835 | 31.7   | 805 | 211.2 | 5365 | 51.7                       | 24x2 | 200                              | 4000                       |
|         |    |       |      |            |      |     |      |      |        |     |       |      | 41.0                       |      | 29                               | 8818                       |



# MAXAM MS950A

BIAS PLY TRACTOR TIRE R1

Designed primarily for compact tractors, with dual capability for both muddy field and dryland operations.

- ▶ High-strength carcass material provides excellent load-carrying capacity.
- ▶ Lightweight construction offers fuel efficiency and cost-effectiveness.
- ▶ Segmented lug angle design balances strong traction with stable handling.
- ▶ Reinforced groove base and sidewalls features ribs that enhance self-cleaning performance and visual appeal.
- ▶ Premium compound significantly improves puncture resistance and aging resistance.



## TIRE TECHNICAL SPECIFICATIONS & APPLICATIONS



| Size   | PR | LI/SS | TYPE | RIM (Rec.) | S.W. |       | O.D. |       | S.L.R. |     | R.C   |      | TREAD DEPTH<br>32NDS<br>mm | Lugs | Inflation Pressure<br>kPa<br>psi | Load Capacity<br>kg<br>lbs |
|--------|----|-------|------|------------|------|-------|------|-------|--------|-----|-------|------|----------------------------|------|----------------------------------|----------------------------|
|        |    |       |      |            | in   | mm    | in   | mm    | in     | mm  | in    | mm   |                            |      |                                  |                            |
| 8-16   | 6  | 91A6  | TT   | 6L         | 8.3  | 210.0 | 31.1 | 790   | 14.3   | 362 | 95.0  | 2413 | 37.8                       | 13x2 | 190                              | 615                        |
|        |    |       |      |            |      |       |      |       |        |     |       |      | 30.0                       |      | 28                               | 1356                       |
| 8-18   | 6  | 94A6  | TT   | W6         | 8.3  | 210.0 | 33.1 | 840   | 15.3   | 389 | 102.1 | 2593 | 37.8                       | 14x2 | 190                              | 670                        |
|        |    |       |      |            |      |       |      |       |        |     |       |      | 30.0                       |      | 28                               | 1477                       |
| 9.5-16 | 6  | 96A6  | TT   | W8L        | 9.5  | 241.0 | 33.3 | 845.0 | 14.7   | 374 | 98.3  | 2496 | 41.6                       | 13x2 | 210                              | 710                        |
|        |    |       |      |            |      |       |      |       |        |     |       |      | 33.0                       |      | 30                               | 1565                       |