

TUE302+



- Wide pattern design is equipped with super tear resistance and wear resistance capacity.
- High self-cleaning capacity.
- Tire tread provides good flexibility, cut resistance and chip resistance capacity.
- Reinforced sidewall design increase stability and anti-puncture capability.
- Optimized-tuned to enhance stability, life time and smooth running.



Longer
Tire Life




Enhanced
Sidewall



Self
Cleaning



Stability



Special
Compound



Wear
Resistance
Compound



Cut&Chip
Resistance
Compound



TUE302+

Tire Size	TT/TL	Rim	TRA	Load/Speed Index	Star Rating	Tread Depth (mm/32ND)	Outer Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (Kpa/PSI)	Load Capacity (Kg/Lbs)	Speed (Km/mph)
750/65R25	TL	24.00/3.0	E-3/L-3	190B	★★	44	1610	754	425	10600	50
						55	63.4	29.7	62	23400	30
				209A2	★★	44	1610	754	625	18500	10
						55	63.4	29.7	91	40800	5
29.5R29	TL	25.00/3.5	E-3/L-3	202B	★★	44	1975	750	525	15000	50
						55	77.8	29.5	76	33100	30
				218A2	★★	44	1975	750	650	23600	10
						55	77.8	29.5	94	52000	5