

BACKTRACK RADIAL SUPREME



- Strong tread lugs for severe applications
- High traction on hard and abrasive surfaces
- Reinforced lug base and middle for severe applications
- Durable tire
- Robust and reinforced shoulders for advanced stability and cut resistance
- Special bead protection



Reinforced
Shoulder



Cut & Chip
Resistance



Excellent
Traction



Durability



Stability



BACKTRACK RADIAL SUPREME

Tire Size	TT/TL	Rim	TRA	Load/Speed Index	Tread Depth (mm/32ND)	Outer Diameter (mm/inch)	Section Width (mm/inch)	Inflation Pressure (Kpa/PSI)	Load Capacity (Kg/Lbs)	Speed (Km/mph)
280/80R18 (10.5/80R18)	TL	W9	R-4	132A8/132B	28.0	914	288	400	2000	50
340/80R18 (12.5/80R18)	TL	11.00	R-4	143A8/143B	30.0	996	353	400	2725	50
400/70R18 (405/70R18)	TL	13.00	R-4	147A8/147B	33.0	1020	408	400	3075	50
280/80R20 (10.5/80R20)	TL	W9	R-4	133A8/133B	28.0	967	285	400	2060	50
340/80R20 (12.5/80R20)	TL	11.00	R-4	144A8/144B	30.0	1053	356	400	2800	50
380/75R20 (14.5R20)	TL	W12	R-4	148A8/148B	33.0	1088	386	400	3150	50
400/70R20 (16.0R20)	TL	13.00	R-4	149A8/149B	33.0	1072	408	400	3250	50
*400/70R20 (16.0R20)	TL	13.00	R-4	149A8/149B	33.0	1072	408	400	3250	50
400/70R24 (16.0R24)	TL	13.00	R-4	152A8/152B	33.0	1172	407	400	3550	50
440/80R24 (16.9R24)	TL	DW13, DW14L	R-4	161A8/161B	36.0	1312	457	400	4625	50

BACKTRACK RADIAL SUPREME										
Tire Size	TT/TL	Rim	TRA	Load/Speed Index	Tread Depth (mm/ 32ND)	Outer Diameter (mm/ inch)	Section Width (mm/ inch)	Inflation Pressure (Kpa/ PSI)	Load Capacity (Kg/ Lbs)	Speed (Km/ mph)
460/70R24 (17.5LR24)	TL	DW15L	R-4	159A8/159B	36.0	1247	468	400	4375	50
500/70R24 (19.5LR24)	TL	DW16L	R-4	164A8/164B	36.0	1317	505	400	5000	50
540/70R24	TL	DW16L, DW18L	R-4	168A8/168B	36.0	1364	536	400	5600	50
480/80R26 (18.4R26)	TL	DW15L	R-4	160A8/160B	36.0	1412	497	320	4500	50
440/80R28 (16.9R28)	TL	DW13, DW14L	R-4	156A8/156B	36.0	1416	456	320	4000	50
				163A8/163B				400	4875	

*:With Steel Belt