



Aggressive lug design with large blocks at tread center provides excellent traction and braking on rough roads with mud or gravel and is self-cleaning for ease of maintenance.

Applicable in mining, logging, construction or rock and quarry operations with some very short on high-way use possible.

Special tread compounds resist chipping and chunking in rugged off-road conditions.



MT100

TIRE SIZE	LR/PR	SERVICE INDEX	TREAD DEPTH	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH	TREAD SURFACE WIDTH	Max. Load Capacity at Cold Inflation Pressure							
								SINGLE				DAUL			
								(Kg)	(lbs)	(KPa)	(PSI)	(Kg)	(lbs)	(KPa)	(PSI)
10.00R20	J/18	149/146F	24.0	7.5	1065	278	210	3250	7160	930	135	3000	6610	930	135
11.00R20	J/18	152/149F	24.5	8	1096	293	220	3550	7825	930	135	3250	7165	930	135
12.00R20	J/18	154/151F	25.5	8.5	1136	315	235	3750	8270	830	120	3450	7610	830	120
12.00R24	L/20	160/157F	25.0	8.5	1226	315	234	4500	9920	900	131	4125	9090	900	131



MT200

3 circumferential grooves ensures good directional stability, even wear and smooth ride.

Heavy siping provides good braking stability and high lateral traction on wet and dry surface.

Improved tread compound helps resist tears and ensure good mileage in on and off road use.

Sidewall reinforcing ribs protects against impacts and scuffing.



TIRE SIZE	LR/PR	SERVICE INDEX	TREAD DEPTH	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH	TREAD SURFACE WIDTH	Max. Load Capacity at Cold Inflation Pressure							
								SINGLE				DAUL			
								(Kg)	(lbs)	(KPa)	(PSI)	(Kg)	(lbs)	(KPa)	(PSI)
7.50R16	G/14	122/118L	12.0	6.00G	805	215	160	1500	3305	770	112	1320	2910	770	112
10.00R20	J/18	149/146J	16.0	7.5	1054	278	214	3250	7160	930	135	3000	6610	930	135
11.00R20	J/18	152/149K	16.0	8	1085	293	224	3550	7825	930	135	3250	7165	930	135



Aggressive lug design with large blocks at tread center provides excellent traction and braking on rough roads with mud or gravel and is self-cleaning for ease of maintenance.

Applicable in mining, logging, construction or rock and quarry operations with some very short on high-way use possible.

Special tread compounds resist chipping and chunking in rugged off-road conditions.



MT100 MAX

TIRE SIZE	LR/PR	SERVICE INDEX	TREAD DEPTH	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH	TREAD SURFACE WIDTH	Max. Load Capacity at Cold Inflation Pressure							
								SINGLE				DAUL			
								(Kg)	(lbs)	(KPa)	(PSI)	(Kg)	(lbs)	(KPa)	(PSI)
12.00R24	L/20	160/157F	32.0	8.5	1238	315	245	4500	9920	900	131	4125	9090	900	131




MT300

Special tread compounds resist chipping and chunking in rugged off-road conditions.

Robust tread block help promote traction and floatation capacity on rough roads.

Applicable for low speed mining service.



TIRE SIZE	LR/PR	SERVICE INDEX	TREAD DEPTH	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH	TREAD SURFACE WIDTH	Max. Load Capacity at Cold Inflation Pressure							
								SINGLE				DAUL			
								(Kg)	(lbs)	(KPa)	(PSI)	(Kg)	(lbs)	(KPa)	(PSI)
7.50R16	L/14	122/118L	15.5	6.00G	808	220	170	1500	3305	770	112	1320	2910	770	112
10.00R20	J/18	149/146J	18.0	7.5	1065	278	214	3250	7610	930	135	6610	6610	930	135



Aggressive lug design with large block at tread center provides excellent traction and braking on rough roads with mud or gravel and is self-cleaning for ease of maintrance.

Applicable in logging, mining, construction or rock and quarry operations with some very short on high-way use possible.

Special tread compounds resist chipping and chunking in rugged off-road conditions.



MT400

TIRE SIZE	LR/PR	SERVICE INDEX	TREAD DEPTH	STANDARD RIM	OVERALL DIAMETER	SECTION WIDTH	TREAD SURFACE WIDTH	Max. Load Capacity at Cold Inflation Pressure							
								SINGLE				DAUL			
								(Kg)	(lbs)	(KPa)	(PSI)	(Kg)	(lbs)	(KPa)	(PSI)
12.00R20	J/18	154/151F	24.0	8.5	1136	315	240	3750	8270	830	120	3450	7610	830	120
12.00R24	L/20	160/157F	27.5	8.5	1238	315	240	4500	9920	900	131	4125	9090	900	131